

MW Twinseal Vinyl Sliding Glass Door

Date: October 1999

Revised:

MW Twinseal® Sliding Patio Doors



Twinseal's advanced Hollow PVC Design stands up to the elements and requires virtually no maintenance. The classic white interior and exterior finish are impact resistant and never need painting. Twinseal's 3/4" Warm Edge Insulating Glass provides energy efficient performance in all seasons, all regions.



WINDOWS & DOORS

MW Manufacturers Inc.

PO Box 559, Rocky Mount, VA 24151-0559

(800) 999-8888 or (540) 483-0511

www.mwwindows.com

MW WINDOWS *Specifications* MW WINDOWS

- > Classic patio door design complements an array of architectural styles.
- > Fully welded corners on frame and sash add strength and durability.
- > Superior rigidity and squareness allow quick, easy installation.
- > Dual Seal Weather Stripping System creates two weather barriers for maximum weatherability.
- > Space saving sliding door design.
- > Energy efficient 3/4" Warm Edge Insulating Glass.
- > Full complement of glazing options — Low-E, Tinted, Low-E/Tinted, and Low-E/Argon.
- > Available Grilles-Between-The-Glass provide a classic divided light appearance. Light patterns in accent windows — including transoms and ellipticals — align for a balanced look.
- > Classic color in white.
- > Left or right operating door design. Field reversible prior to installation.
- > Snap-on accessories provide enhanced trim options and means for joining with accent windows.
- > Fiber mesh screen on locking white aluminum frame.
- > Matching white powder-coat handles with keyed lock option. Available brass handle for the interior.
- > MW Twinseal Vinyl Patio Doors are stringently tested for structural performance in accordance with AIAA/AMA 101-93. Performance on 6-0 x 6-8 doors meets SGD-840; performance on 8-0 x 6-8 doors meets SGD-835.

Sizes and Rough Openings

SINGLE STATIONARY PANELS

Unit Designation		2-6	3-0	4-0
6-8	Rough Opening	2'-9 3/8"	3'-3"	4'-1 3/4"
	Unit Dimension	2'-8 3/8"	3'-2"	4'-2 3/4"
		X	X	X

SLIDING DOUBLE PANEL UNITS

Unit Designation		5-0	6-0	8-0
6-8	Rough Opening	5'-0 7/16"	5'-11 11/16"	8'-1 3/16"
	Unit Dimension	4'-11 7/16"	5'-10 11/16"	8'-0 3/16"
		X	X	X